KP PUSHBUTTON SERIES SAMPLE VALVE

FOR PRESSURIZED OIL AND COOLANT APPLICATIONS



FOR PRESSURIZED OIL AND COOLANT SYSTEM APPLICATIONS

The KP Pushbutton Series sample valve can be used to take samples on operating equipment with no sample probe needed. Sample valves allow you to reduce the time needed to extract a sample, while gaining a more representative sample and avoiding external contamination for a more accurate oil analysis result.

APPLICATIONS

- Engines
- Transmissions
- Coolant
- Hydraulics
- Compressors
- Turbines

FEATURES

- Patented elastomeric vacuum tight valve seals
- Reliable dual sealed design tested at 7,800 psi for one million cycles
- Automatic valve shut off
- Low purge volume
- Carbon steel with Corrosion resistant zinc-nickel plating
- Locknut available for extra protection against high vibration

SPECIFICATIONS

- Sampling Range: 5 -750 psi (0.03 5.17 MPa)
- Working Pressure: 6000 psi (41.4 MPa)
- Seal Material Temperature Range:
 - Nitrile: -40C 115C (-40F 239F)
 - Viton: -26C 204C (-15F 400F)
 - EPDM: -50°C 150°C (-58F 302F)
- Valve Material: Carbon steel with corrosion resistant zinc nickel plating
- Valve Overall Size (L x W): 2" x 1.5" (approx.)

FLUID & LIFE



ALL WAYS RELIABLE.

KP PUSHBUTTON SERIES SAMPLE VALVE

FOR PRESSURIZED OIL AND COOLANT APPLICATIONS

AVAILABILITY	PART	DESCRIPTION	IMAGE
ln Stock Special Order Special Order Special Order Special Order	100145 / CHK-KP18N 100146 / CHK-KP18NV CHK-KPL18NV 101165 / CHK-KP18NV-R CHK-KP18NE	Sample Valve, KP Pushbutton. 1/8" - 27 NPTF Nitrile Seal, Steel (Zinc-Nickel finish) Viton Seal, Steel (Zinc-Nickel finish) Locknut, Viton Seal, Steel (Zinc-Nickel finish) Viton Seal, 316 Stainless Steel EDPM Seal, Steel (Zinc-Nickel finish)	Pushbutton
In Stock Special Order Special Order Special Order Special Order	100141 / CHK-KP14N 100142 / CHK-KP14NV CHK-KPL14NV CHK-KP14NE CHK-KPQ14NP	Sample Valve, KP Pushbutton. 1/4" - 18 NPTF Nitrile Seal, Steel (Zinc-Nickel finish) Viton Seal, Steel (Zinc-Nickel finish) Locknut, Viton Seal, Steel (Zinc-Nickel finish) EDPM Seal, Steel (Zinc-Nickel finish) For Refrigeration & Ammonia Compressors, Neoprene Seal, Steel (E-Nickel Plated)	Locknut
Special Order Special Order Special Order	100150 / CHK-KP716U 101218 / CHK-KP716UV CHK-KPL716UV	Sample Valve, KP Pushbutton. 7/16" - 20 ORB Nitrile Seal, Steel (Zinc-Nickel finish) Viton Seal, Steel (Zinc-Nickel finish) Locknut, Viton Seal, Steel (Zinc-Nickel finish)	
Special Order Special Order Special Order	100153 / CHK-KP916U CHK-KP916UV CHK-KPL916UV	Sample Valve, KP Pushbutton. 9/16" - 18 ORB Nitrile Seal, Steel (Zinc-Nickel finish) Viton Seal, Steel (Zinc-Nickel finish) Locknut, Viton Seal, Steel (Zinc-Nickel finish)	and the second sec
Special Order Special Order Special Order Special Order	101077 / CHK-KP101MV CHK-KPL101MV 100140 / CHK-KP1415MV CHK-KPL1415MV	Sample Valve. KP Pushbutton, Metric M10x1, Viton Seal, Steel (Zinc-Nickel finish) Locknut, M10x1, Viton Seal, Steel (Zinc-Nickel finish) M14x1.5, Viton Seal, Steel (Zinc-Nickel finish) Locknut, M14x1.5, Viton Seal, Steel (Zinc-Nickel finish)	
Special Order	100175 / CHK-LP4N	Sample Valve, LP Pushbutton. Sampling Pressure: 3 psi (low viscosity) - 125 psi (0.02 - 0.86 MPa). 1/4" - 18 NPTF. Viton seal, Steel (Zinc-Nickel finish)	
Special Order	100148 / CHK-KP4PT	Pushbutton Spout Barb For use with standard plastic tubing	
In Stock	100428 / POG-JAR 100861 / SCA-PINTPURGE	Flush Jar. 38mm thread compatible with standard sample pump. 100 ml 500 ml	

Note: Other thread sizes, valve body and seal materials are available by special order. Viton seal valves are recommended for engine and transmission applications. EPDM seal valves are recommended for engine coolant applications.

FLUID & LIFE EQUIPMENT RELIABILITY SERVICES